


# PAC-1700G

7-slot Full-size Compact Chassis




## Features

- ◆ RoHS compliant design
- ◆ 1 x 5.25", 1 x front accessible 3.5", 2 x 3.5" HDD
- ◆ 1 x 8 cm cooling fan
- ◆ 7 expansion slots, compatible with full-size SBC




Replaceable fan filter



8 cm cooling fan



## Dimensions



## Specifications

◆ Construction	Metal with plastic front panel
◆ SBC Form Factor	Full-size, slot CPU card
◆ Drive Bays	1 x front-accessible 3.5" 1 x 5.25" 2 x 3.5" HDD
◆ Cooling Fans	1 x 8cm
◆ I/O openings	1 x LPT, 2 x COM
◆ Expansion Slots	7 slots
◆ Indicators	Power, HDD
◆ Buttons	power switch, reset
◆ Operating Temperature	0~50°C
◆ Operation Humidity	10% ~ 90%
◆ Color	B: Black
◆ Weight (Net/ Gross)	6kg / 8.4kg
◆ Dimension (DxWxH)	433mm x 233mm x 253.7mm

## Backplane Options

Model No.	SBC Type	PCI	ISA	PCIe			PSU Connector
				x1	x4	x16	
IP-7SA-RS-R30	PCISA	4	2	0	0	0	AT
PCI-7S-RS-R30	PICMG 1.0	4	3	0	0	0	AT/ATX
PE-6S	PICMG 1.3	2	0	1	1	1	ATX
PE-7S	PICMG 1.3	3	0	2	0	1	ATX
PE-7S2	PICMG 1.3	1	0	4	0	1	ATX
HPE-7S1	PCI/PIC0e	4	0	2	0	1	ATX

## Power Supply Options

Type	Model No.	Watt
AT	ACE-925AP-U-RS	250W
	ACE-940AP-RS	390W
ATX	ACE-832AP-RS	300W
	ACE-841AP-S-RS	400W

PAC-1700G can support single PS/2 PSU. For more models of IEI PSU, please visit [www.ieiworld.com](http://www.ieiworld.com).

## Ordering Information

Part No.	Description
PAC-1700GB/ ACE-832AP	7-slot full-size chassis, black, with ACE-832AP-RS, RoHS